

### SPECIFICATIONS FOR ARGO HUNTMASTER 8X8

Engine		Kohler Aegis LH 775
Engine Warranty		3 year
		4 cycle OHV V-Twin gasoline EFI engine, electronic ignition, full pressure lubrication and oil filter
Horsepower		30
Displacement		747 cc
Cooling		Liquid Cooled
		Electric
Brakes		Hydraulic
Steering		One-piece, ergonomic handlebar. Steering control features hand brake. For safety and ease of handling, the ARGO steering transmission provides continuous torque to all axles.
Controls		Right-hand twist grip throttle. Light switch and ignition switch.
Clutch		Belt-driven, Continuously Variable Transmission (CVT) maximizes engine power to the transmission.
Transmission		ADMIRAL 7
Drive System		Roller chain drive machined sprockets are spline-fit onto 1 3/8" diameter axles and are protected with triple-sealed greaseable bearings.
Frame		Formed steel channel construction, welded for high strength and durability. Protected with Bonderite® M-PP 930™ epoxy-acrylic autodeposition coating.
Body		Vacuum formed High Molecular Weight Polyethylene
Full Skid Plate		Standard
Load Capacity 1	On Land	1,000 lb. (454 kg)
	On Water	900 lb. (410 kg)
Towing Capacity <sup>2</sup>		1,800 lb. (816 kg)
Seating Capacity <sup>3</sup>	On Land	6 persons
	On Water	4 persons
Fuel Capacity		7.1 US gallons (27 litres) See-through polyethylene fuel tank. 8 hrs. operation 4
Speed <sup>5</sup>	On Land	20 mph (32 km per hour)
	On Water <sup>6</sup>	3 mph (5 km per hour)
Shipping Weight		1,380 lb. (626 kg)
Dimensions (L X W X H)		124 x 60 x 52" (3,150 x 1,524 x 1,321 mm)
Axle Bearing Extensions		Front - Standard, Rear - Standard
Instrumentation		LCD Digital Gauge Cluster: Speedometer, Odometer, Voltmeter, Hour Meter, Tachometer, Low Oil Pressure and Parking Brake Reminder Lights
Tires		ARGO AT189 25x12.00-9 NHS
Ground Pressure		1.7 psi (13.5 kPa) using tires 0.67 psi (4.6 kPa) using tracks
Ground Clearance	Tires	9.5" (240 mm)
	Tracks	11" (279 mm)
Operating Conditions		All weather, all terrain, -40°F to +104°F (-40°C to +40°C)

The ARGO HuntMaster 8x8 builds on the ARGO 8x8 750 HDi platform to create a high powered go-anywhere package with practical detailing to enhance every hunting experience.

#### Standard vehicle features:


- Soft ride system to run low-pressure tires with new beadlock aluminum rims
- Robust brushguard provides outstanding protection for the front end of the vehicle, absorbing impacts from off-road hazards such as brush, branches, and more.
- 3,500 lb. (1,588 kg) WARN Winch
- Dual side entry steps to assist in vehicle entry and exit when outfitted with gear, backpack and guns
- Dual USB power outlet, for riders to charge their phones, play digital media and utilize their GPS
- Interior lighting package to illuminate front driving area, vehicle console and rear cargo area
- Bilge Pump


#### Included HuntMaster upgrades:

- Upgraded triple differential ADMIRAL steering transmission capable of reaching top-end speed of 25 mph (39.5 km/hr)
- Mounted two gun Sure Grip gun rack to ensure the safe transportation of firearms to the best hunting grounds
- 2-position, fold-down rear rack for extra storage of cargo and game
- Easily removable hood rack capable of carrying cargo, blinds and trophies to and from the hunt
- Upgraded front and rear seat cushions with a front seat backrest pad featuring refined stitching and custom embossing of the ARGO logo
- Heavy duty skid plate for added insurance against lower body damage
- Enhanced lighting package featuring dual high powered floodlights
- Brake lights

## DIMENSIONS

Dimensions are approximate and dependent on final build specification.





# AVAILABLE ARGO COLOR













Proud to be located in



220 Bergey Court, New Hamburg ON, Canada N3A 2J5 Toll Free: 1-877-274-6288 Tel: (519) 662-4000 Fax: (519) 662-2421 www.ARGOxtv.com/HuntMaster

- 1 Capacity includes occupants, cargo, outboard motor and fuel, and installed accessories
- Max. outboard motor size 7.4 kW (9.9 hp).
- 2 Towing capacity is approximate and depends on type of surface, load on vehicle as well as incline. Max Hitch Tongue Load (when equipped with hitch) 100 lb. (45 kg) for all models Subject to rear compartment load capacity limitations.

- Fuel consumption depends on load and operating conditions.
  All speeds are approximate and depend on conditions.
  All speeds are approxed Personal Floatation Device (PFD) when operating in water or on ice.
  ADMIRAL triple differential steering transmission with dedicated Hi and Low selector; Forward, Neutral, Reverse,

Some vehicle applications shown are for demonstration purposes, originating from third parties and not available from ARGO. In all cases vehicle load limits have been considered. For safety, always wear approved helmets and eve protection. When operating in water, always wear approved Personal Floatation Devices. Always remain seated while in the ARGO. When equipped with tracks, HuntMaster models are not fully amphibious, however water crossing is possible with a fording depth of 26" (660 mm). • Printed in Canada 11/2015



tread lightly! ON LAND AND WATER



