



2022 CONQUEST PRO SERIES



Designed to withstand the demanding nature of commercial work and proven to work as hard as your team, ARGO is pleased to announce the return of the Conquest Pro Series for model year 2022. Equipped with features that cater to the commercial market, the Conquest Pro series is engineered to withstand the test of time.

Durability and structural integrity are at the heart of every Conquest Pro model and are outfitted with engine options worthy to take on the toughest jobs. Available in either the 800 EFI (30HP) V-Twin liquid cooled engine or the 950 EFI (40HP) V-Twin fan cooled engine, these dependable powerplants are designed to operate in the harshest of conditions. Increased alternator output available on all Conquest Pro models also provide an impressive 50 AMPS on 950s and 60 AMPS on 800's for powering additional accessories and implements without interruption or hesitation.

For model year 2022, ARGO has focused on maximizing engine torque, acceleration and speed. In pursuit of achieving this goal, Argo's team of engineers has developed the ARGO Instant Torque Drive System (ITDS). The ITDS incorporates the new ARGO Instant Torque Clutch (ITC) and is paired with the advanced Admiral transmission. This pairing delivers dramatically improved performance to your XTV that is extremely noticeable the moment you grab the throttle. The ITC works to load the engine maintaining and enhancing peak torque equating in a significant increase in both acceleration and torque. Proven to offer superior performance, the ITDS and ITC alleviate the need for a High torque (HT) transmission while offering the speed advantages of the Standard Torque (ST) transmission. The ARGO Conquest Pro Series capabilities far exceed the expectations of skilled professionals working within the commercial markets. Offering the largest footprint and greatest versatility within the XTV commercial market the Conquest Pro Series is built with reinforced steel beam exterior construction and is capable of hauling load capacities up to 1,210 pounds. With a 2,000-lb towing capacity, you are able to take what you need to Go Anywhere with the Conquest Pro Series.

The enduring Admiral transmission available in the Conquest Pro Series comes available from the factory with a torque configuration that provides superior results when put to the test. Trusted after years of experience in grueling conditions, the Admiral transmission is a real workhorse and ideal when faced with the challenges of tackling extreme terrain. The selectable High/Low transmission allows the driver to choose between steering smoothly for fast moving ground travel or benefit from zero-radius turning for navigating challenging terrain in confined, tight-to-work spaces.

When down time impacts your profitability, reliability becomes exceedingly crucial. The Conquest Pro Series auto chain lubrication system and oil-filled axles simplifies routine maintenance to ensure smooth, dependable operation regardless of the environment or the demands of the operator.

Legendary ARGO high ground clearance and rugged capabilities gives you the confidence knowing your work crew can trek further and come home safely. The high-density polyethylene body and skid plate with heavy-duty welded steel brush-guard protect the Conquest Pro Series and its passengers from trail hazards and undercarriage damage. 25-inch XT119 tires are mounted to ARGO's signature AirLock steel offset rims ensuring the tire remains firmly fixed to the rim in rugged terrain while allowing operators to adjust tire pressure to the terrain while providing a 30% smoother ride.

\<u>\</u>|**0**|U

Accessory heavy-duty rubber tracks easily install around existing tires and provide optimum floatation over snow and swamp with minimal ground pressure. The lightweight design also provides exceptional traction and low-rolling resistance.

The Conquest Pro Series comes equipped with a 4,500-lb WARN® winch mounted to the heavy-duty commercial grade brushguard along with an extended range fuel tank with a 8.5-gallon capacity. Optimized to meet the differentiated needs of the commercial market, the Conquest Pro Series is engineered to enhance your teams' efficiency while offering a safer solution when going where others can't.





Admiral Transmission

Conquest Pro Series features the premium Admiral transmission, which employs a sophisticated gearing system and dual differentials on the output shafts. When steering, the braking force is applied to a steering differential (rather than the output shafts), translating into smoother and gentler steering. Every ARGO transmission is designed and built by its parent company, Ontario Drive & Gear Limited – the world leader in precision gearing and high-performance transmissions – to ensure the best reliability, maintainability and smooth, efficient transfer of power to the ground.

New Instant Torque Drive System (ITDS) & Instant Torque Clutching (ITC)

The ARGO Instant Torque Drive System (ITDS) delivers dramatically improved performance by coupling the New ARGO Instant Torque Clutch (ITC) with the versatile Admiral transmission. The Instant Torque Clutch (ITC) loads the engine to maintain peak torque resulting in increased acceleration and enhanced torque. Alleviating the need for a High Torque (HT) transmission while maximizing the appealing capabilities of the Standard Torque (ST) transmission, we have combined acceleration, torque and speed into one package.



Auto Chain Lubrication

Simplifying routine maintenance, the auto chain lubrication disperses oil automatically onto your machine's chain driven system at intervals of 5 seconds every 60 minutes of operation. This process alleviates the need to manually grease your chains at scheduled intervals while providing satisfactory lubrication at all times.



4,500 lb. WARN Winch

The Conquest Pro series is equipped with a mighty 4,500-lb WARN winch making it the highest rated winch available on a commercial XTV. The winch is conveniently operated via an on-dash actuator.



Alternator

The commercial grade alternator comes standard on the Conquest Pro Series and offers 60 amps on the 800 models and 50 amps on 950 models.

Heavy Duty Axle

The Conquest Pro Series features heavy-duty 1.5" forged axles in oil bath hubs along with reinforced housings to accommodate heavy commercial applications.

Power Dump Box

The Conquest Pro XT-X solid steel power dump box can move bulk loads with a capacity of 1,000 lbs. [450 kg].









ENGINE	
CYLINDER	V-Twin
FUEL SYSTEM	EFI
COOLING	Liquid Cooled
ALTERNATOR OUTPUT (MAX)	60 AMPS
MAX. POWER	30HP
DRIVETRAIN	
TRANSMISSION TYPE	Admiral
DRIVE BELT	Heavy Duty
SERVICE BRAKES	Hydraulic
STEERING BRAKES	Hydraulic
BRAKE COOLING FAN	Accessory
AUTO CHAIN LUBRICATION	Standard
SPEED ON LAND	17 mph (27 km/h)
SPEED ON WATER	3 mph (5 km/h)

DIMENSIONS/WEIGHT	
LENGTH	125 in (3,175 mm)
WIDTH	65 in (1,651 mm)
HEIGHT	49 in (1,245 mm)
LOAD CAPACITY - LAND	1,210 lbs (549 kg)
LOAD CAPACITY - WATER	510 lbs (231 kg)
TOWING CAPACITY	2,000 lbs (816 kg)
FUEL TANK CAPACITY	8.5 gal (32 L)
RIDER CAPACITY - LAND	2
RIDER CAPACITY - WATER	2
TIRES & WHEELS	
TIRES ARGO	XT119 25 x 12 - 9
WHEEL	Steel AirLock
GROUND CLEARANCE - TIRES	9 in (228 mm)
GROUND CLEARANCE - TRACKS	10 in (254 mm)
GROUND PRESSURE - TRACKS	1.06 psi (7.3 kPa)

FRONT RACK	Accessory
BRUSHGUARD	Standard
WINCH	4,500 lbs
FULL SKID PLATE	Standard
BILGE PUMP	Standard
ENTRY STEP	Accessory
AVAILABLE COLORS	Green, Industrial Yellow







ENGINE	
CYLINDER	V-Twin
FUEL SYSTEM	EFI
COOLING	Fan Cooled
ALTERNATOR OUTPUT (MAX)	50 AMPS
MAX. POWER	40HP
DRIVETRAIN	
TRANSMISSION TYPE	Admiral
DRIVE BELT	Heavy Duty
SERVICE BRAKES	Hydraulic
STEERING BRAKES	Hydraulic
BRAKE COOLING FAN	Accessory
AUTO CHAIN LUBRICATION	Standard
SPEED ON LAND	17 mph (27 km/h)
SPEED ON WATER	3 mph (5 km/h)

125 in (3,175 mm)
65 in (1,651 mm)
49 in (1,245 mm)
1,210 lbs (231 kg)
510 lbs (231 kg)
2,000 lbs (816 kg)
8.5 gal (32 L)
2
2
XT119 25 x 12 - 9
Steel AirLock
9 in (228mm)
10 in (254 mm)
1.06 psi (7.3 kPa)

FEATURES	
FRONT RACK	Accessory
BRUSHGUARD	Standard
WINCH	4,500 lbs
FULL SKID PLATE	Standard
BILGE PUMP	Standard
ENTRY STEP	Accessory
AVAILABLE COLORS	Green, Industrial Yellow







ENGINE	
CYLINDER	V-Twin
FUEL SYSTEM	EFI
COOLING	Liquid Cooled
ALTERNATOR OUTPUT (MAX)	60 AMPS
MAX. POWER	30HP
DRIVETRAIN	
TRANSMISSION TYPE	Admiral
DRIVE BELT	Heavy Duty
SERVICE BRAKES	Hydraulic
STEERING BRAKES	Hydraulic
BRAKE COOLING FAN	Accessory
AUTO CHAIN LUBRICATION	Standard
SPEED ON LAND	17 mph (27 km/h)

DIMENSIONS/WEIGHT	
LENGTH	125 in (3,175 mm)
WIDTH	65 in (1,651 mm)
HEIGHT	80.5 in (2,045 mm)
LOAD CAPACITY - LAND	1,048 lbs (475 kg)
LOAD CAPACITY - WATER	N/A
TOWING CAPACITY	2,000 lbs (816 kg)
FUEL TANK CAPACITY	8.5 gal (32 L)
RIDER CAPACITY - LAND	2
TIRES & WHEELS	
TIRES ARGO	XT119 25 x 12 - 9
WHEEL	Steel AirLock
GROUND CLEARANCE - TIRES	9 in (228mm)
GROUND CLEARANCE - TRACKS	10 in (254 mm)
GROUND PRESSURE - TRACKS	1.06 psi (7.3 kPa)

FEATURES	
FRONT RACK	Accessory
BRUSHGUARD	Standard
WINCH	4,500 lbs
ROPS	Standard
REAR MESH	Standard
ROOF	Standard
POWER DUMP BOX	Accessory
FULL SKID PLATE	Standard
BILGE PUMP	Standard
ENTRY STEP	Accessory
AVAILABLE COLORS	Green, Industrial Yellow







ENGINE	
CYLINDER	V-Twin
FUEL SYSTEM	EFI
COOLING	Fan Cooled
ALTERNATOR OUTPUT (MAX)	50 AMPS
MAX. POWER	40HP
DRIVETRAIN	
TRANSMISSION TYPE	Admiral
DRIVE BELT	Heavy Duty
SERVICE BRAKES	Hydraulic
STEERING BRAKES	Hydraulic
BRAKE COOLING FAN	Accessory
AUTO CHAIN LUBRICATION	Standard
SPEED ON LAND	17 mph (27 km/h)

DIMENSIONS/WEIGHT	
LENGTH	125 in (3,175 mm)
WIDTH	65 in (1,651 mm)
HEIGHT	80.5 in (2,045 mm)
LOAD CAPACITY - LAND	1,048 lbs (475 kg)
LOAD CAPACITY - WATER	N/A
TOWING CAPACITY	2,000 lbs (816 kg)
FUEL TANK CAPACITY	8.5 gal (32 L)
RIDER CAPACITY - LAND	2
TIRES & WHEELS	
TIRES ARGO	XT119 25 x 12 - 9
WHEEL	Steel AirLock
GROUND CLEARANCE - TIRES	9 in (228mm)
GROUND CLEARANCE - TRACKS	10 in (254 mm)
GROUND PRESSURE - TRACKS	1.06 psi (7.3 kPa)

FEATURES	
FRONT RACK	Accessory
BRUSHGUARD	Standard
WINCH	4,500 lbs
ROPS	Standard
REAR MESH	Standard
ROOF	Standard
POWER DUMP BOX	Accessory
FULL SKID PLATE	Standard
BILGE PUMP	Standard
ENTRY STEP	Accessory
AVAILABLE COLORS	Green, Industrial Yellow







ENGINE	
CYLINDER	V-Twin
FUEL SYSTEM	EFI
COOLING	Liquid Cooled
ALTERNATOR OUTPUT (MAX)	60 AMPS
MAX. POWER	30HP
DRIVETRAIN	
TRANSMISSION TYPE	Admiral
DRIVE BELT	Heavy Duty
SERVICE BRAKES	Hydraulic
STEERING BRAKES	Hydraulic
BRAKE COOLING FAN	Accessory
AUTO CHAIN LUBRICATION	Standard
SPEED ON LAND	17 mph (27 km/h)

DIMENSIONS/WEIGHT	
LENGTH	125 in (3,175 mm)
WIDTH	65 in (1,651 mm)
HEIGHT	80.5 in (2,045 mm)
LOAD CAPACITY - LAND	848 lbs (385 kg)
LOAD CAPACITY - WATER	N/A
TOWING CAPACITY	2,000 lbs (816 kg)
FUEL TANK CAPACITY	8.5 gal (32 L)
RIDER CAPACITY - LAND	2
TIRES & WHEELS	
TIRES ARGO	XT119 25 x 12 - 9
WHEEL	Steel AirLock
GROUND CLEARANCE - TIRES	9 in (228mm)
GROUND CLEARANCE - TRACKS	10 in (254 mm)
GROUND PRESSURE - TRACKS	1.06 psi (7.3 kPa)

FEATURES	
FRONT RACK	Accessory
BRUSHGUARD	Standard
WINCH	4,500 lbs
ROPS	Standard
REAR MESH	Standard
ROOF	Standard
POWER DUMP BOX	Standard
FULL SKID PLATE	Standard
BILGE PUMP	Standard
ENTRY STEP	Accessory
AVAILABLE COLORS	Green, Industrial Yellow







ENGINE	
CYLINDER	V-Twin
FUEL SYSTEM	EFI
COOLING	Fan Cooled
ALTERNATOR OUTPUT (MAX)	50 AMPS
MAX. POWER	40HP
DRIVETRAIN	
TRANSMISSION TYPE	Admiral
DRIVE BELT	Heavy Duty
SERVICE BRAKES	Hydraulic
STEERING BRAKES	Hydraulic
BRAKE COOLING FAN	Accessory
AUTO CHAIN LUBRICATION	Standard
SPEED ON LAND	17 mph (27 km/h)

DIMENSIONS/WEIGHT	
LENGTH	125 in (3,175 mm)
WIDTH	65 in (1,651 mm)
HEIGHT	80.5 in (2,045 mm)
LOAD CAPACITY - LAND	848 lbs (385 kg)
LOAD CAPACITY - WATER	N/A
TOWING CAPACITY	2,000 lbs (816 kg)
FUEL TANK CAPACITY	8.5 gal (32 L)
RIDER CAPACITY - LAND	2
TIRES & WHEELS	
TIRES ARGO	XT119 25 x 12 - 9
WHEEL	Steel AirLock
GROUND CLEARANCE - TIRES	9 in (228mm)
GROUND CLEARANCE - TRACKS	10 in (254 mm)
GROUND PRESSURE - TRACKS	1.06 psi (7.3 kPa)

FEATURES	
FRONT RACK	Accessory
BRUSHGUARD	Standard
WINCH	4,500 lbs
ROPS	Standard
REAR MESH	Standard
ROOF	Standard
POWER DUMP BOX	Standard
FULL SKID PLATE	Standard
BILGE PUMP	Standard
ENTRY STEP	Accessory
AVAILABLE COLORS	Green, Industrial Yellow

