

# OFF TO THE BOONIES.



## AURORA PRO XT

The ARGO Aurora Pro XT is a game-changing machine that goes beyond the limitations of traditional transportation, enabling commercial industries to safely achieve the seemingly impossible. With its exceptional load capacity, towing capabilities and advanced safety features, the Aurora Pro XT can effortlessly transport heavy equipment, supplies and personnel to remote locations previously inaccessible. The vehicle's durable rack, brushguard and winch are built to withstand rigorous use. Keep maintenance quick and easy too with its automatic chain lubrication and easy-access grease system, providing reliable performance and reducing downtime. The next big project is waiting. Don't forget to pack your lunchbox.



### AURORA PRO XT HIGHLIGHTS

- KX 800 EFI Liquid Cooled V-Twin Engine
- VX 950 EFI Fan Cooled V-Twin Engine with Hood Fan
- Automatic Admiral Transmission with Triple Differentials
- Instant Torque Drive Systems (ITDS)
- ARGO Progressive Steering (APS)
- XT119 25x12-9 Mud Tires
- Steel Beadlock Wheels
- Heavy-Duty Front Brushguard
- 3,500 lb Winch with Synthetic Rope
- Heavy-Duty Front Rack
- Full-Coverage Roof
- Brake Cooling Fan
- Automatic Chain Lubrication System
- Easy-Access Grease System
- 2" Receiver Hitch
- 1,800 lb. Towing Capacity
- High-Density Polyethylene (HDPE) Body
- Certified Roll-Over Protection Structure (ROPS)

### AURORA TECHNOLOGY



#### ENGINES

The VX 950, fan-cooled, 4-stroke EFI big block V-Twin engine, our highest horsepower engine ever released in an XTV chassis, is an absolute brute for any terrain. The V-Twin, 4-stroke KX 800 engine is liquid cooled and equipped with Electronic Fuel Injection (EFI). Both engines deliver reliable performance in all temperatures and climates.



#### ARGO PROGRESSIVE STEERING (APS)

Operated in conjunction with the Admiral transmission, APS adds a spring element between the handlebars and the brake system to deliver a progressive, dual-rate steering system which results in an easier, smoother turning motion that instills driver confidence while offering improved steering.



#### TRANSMISSION

The ARGO Admiral transmission uses a sophisticated gearing system and triple differentials located on the output shafts. The braking force is applied to a steering differential vs. to the output shafts, translating into smoother and gentler steering.



#### FULLY ENCLOSED BODY

The one-piece, high-density polyethylene (HDPE) lower body is ARGO's signature design feature. The smooth and durable underbody allows for up to 26" of water fording while going over potential snags, stumps and outcrops, delivering unparalleled stability and safe navigation.



#### DRIVETRAIN

The ARGO Instant Torque Drive System (ITDS) delivers outstanding performance by coupling the trusted ARGO Instant Torque Clutch (ITC) with the bulletproof Admiral transmission to deliver increased acceleration and enhanced torque.



#### BEADLOCK WHEELS WITH MUD TIRES

ARGO XT119 25" tires have a proprietary tread pattern for getting through thick, nasty mud and unruly terrain. The innovative ARGO beadlock rims allow for 1.5-psi tire pressure, providing a 30% smoother and more comfortable ride.



**FRONTIER PRO**  
700 XT 8x6



**AURORA PRO**  
800 XT 8x8



**AURORA PRO**  
950 XT 8x8



**CONQUEST PRO**  
800 XT 8x8



**CONQUEST PRO**  
950 XT 8x8



**CONQUEST PRO**  
800 XTL 8x8



**CONQUEST PRO**  
950 XTL 8x8



**CONQUEST PRO**  
800 XTX 8x8



**CONQUEST PRO**  
950 XTX 8x8



**MAGNUM PRO**  
500 XTX

<b>ENGINE</b>	VX 700	KX 800	VX 950	VX 950						
<b>CYLINDER</b>	V-TWIN									
<b>FUEL SYSTEM</b>	EFI									
<b>COOLING</b>	FAN COOLED	LIQUID COOLED	LIQUID COOLED	FAN COOLED						
<b>ALTERNATOR OUTPUT (MAX)</b>	16 AMPS	40 AMPS	50 AMPS	60 AMPS	50 AMPS	60 AMPS	50 AMPS	60 AMPS	60 AMPS	50 AMPS
<b>CHASSIS</b>	6X6	8X8								
<b>SERVICE BRAKES</b>	HYDRAULIC									
<b>STEERING BRAKES</b>	HYDRAULIC									
<b>AUTO CHAIN LUBRICATION</b>	STANDARD									
<b>BRAKE COOLING KIT</b>	STANDARD	STANDARD	STANDARD	N/A						
<b>TRANSMISSION</b>	CLASSIC W/APS	ADMIRAL W/APS	ADMIRAL W/APS	ADMIRAL						
<b>DRIVE BELT</b>	STANDARD	STANDARD	STANDARD	HEAVY DUTY						
<b>FULL SKID PLATE</b>	HEAVY DUTY	HEAVY DUTY	HEAVY DUTY	STANDARD						
<b>BRUSHGUARD</b>	STANDARD									
<b>WINCH</b>	3,500 lb. w/ SYNTHETIC ROPE	3,500 lb. w/ SYNTHETIC ROPE	3,500 lb. w/ SYNTHETIC ROPE	4,500 lb. w/ SYNTHETIC ROPE						
<b>FRONT RACK</b>	STANDARD	STANDARD	STANDARD	ACCESSORY	ACCESSORY	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD
<b>REAR RACK</b>	STANDARD	N/A								
<b>BILGE PUMP</b>	STANDARD									
<b>ROPS</b>	STANDARD	STANDARD	STANDARD	ACCESSORY	ACCESSORY	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD
<b>REAR MESH</b>	N/A	N/A	N/A	ACCESSORY	ACCESSORY	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD
<b>ROOF</b>	N/A	STANDARD	STANDARD	ACCESSORY	ACCESSORY	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD
<b>POWER DUMP BOX</b>	N/A	N/A	N/A	ACCESSORY	ACCESSORY	ACCESSORY	ACCESSORY	STANDARD	STANDARD	STANDARD
<b>LOAD CAPACITY - LAND</b>	440 lb. (200 kg)	635 lb. (288 kg)	705 lb. (320 kg)	1,210 lb. (549 kg)	1,210 lb. (549 kg)	981 lb. (445 kg)	981 lb. (445 kg)	848 lb. (385 kg)	848 lb. (385 kg)	848 lb. (385 kg)
<b>LOAD CAPACITY - WATER</b>	240 lb. (109 kg)	435 lb. (197 kg)	505 lb. (229 kg)	510 lb. (231 kg)	510 lb. (231 kg)	281 lb. (128 kg)	281 lb. (128 kg)	148 lb. (67 kg)	148 lb. (67 kg)	148 lb. (67 kg)
<b>TOWING CAPACITY</b>	1,200 lb. (544 kg)	1,800 lb. (816 kg)	1,800 lb. (816 kg)	2,000 lb. (907 kg)						
<b>SEATING CAPACITY - LAND</b>	2	4	4	2	2	2	2	2	2	2
<b>SEATING CAPACITY - WATER</b>	2	4	4	2	2	2	2	2	2	2
<b>FUEL CAPACITY</b>	8.5 gal. (32 L)									
<b>WATER CAPABILITY</b>	WATER FORDING	WATER FORDING	WATER FORDING	AMPHIBIOUS	AMPHIBIOUS	WATER FORDING				
<b>WEIGHT</b>	1,100 lb. (499 kg)	1,915 lb. (869 kg)	1,845 lb. (837 kg)	1,890 lb. (857 kg)	1,890 lb. (857 kg)	2,119 lb. (961 kg)	2,119 lb. (961 kg)	2,252 lb. (1,021 kg)	2,252 lb. (1,021 kg)	2,252 lb. (1,021 kg)
<b>LENGTH (includes winch when standard)</b>	103 in. (2,616 mm)	126 in. (3,200 mm)	126 in. (3,200 mm)	125 in. (3,175 mm)						
<b>WIDTH</b>	60 in. (1,524 mm)	60 in. (1,524 mm)	60 in. (1,524 mm)	65 in. (1,651 mm)						
<b>HEIGHT</b>	77 in. (1,956 mm)	77 in. (1,956 mm)	77 in. (1,956 mm)	49 in. (1,245 mm)	49 in. (1,245 mm)	80.5 in. (2,045 mm)	80.5 in. (2,045 mm)	80.5 in. (2,045 mm)	80.5 in. (2,045 mm)	80.5 in. (2,045 mm)
<b>AXLE BEARING EXTENSIONS</b>	STANDARD	STANDARD	STANDARD	N/A						
<b>TIRES</b>	ARGO XT119 25X12-9	ARGO XT119 25X12-9	ARGO XT119 25X12-9	ARGO XT117 25X12-9	ARGO XT117 25X12-9	ARGO XT119 25X12-9				
<b>WHEELS</b>	STEEL BEADLOCK									
<b>GROUND CLEARANCE (TIRES)</b>	10 in. (254 mm)	10 in. (254 mm)	9 in. (229 mm)	9 in. (229 mm)	9 in. (229 mm)	9 in. (229 mm)	9 in. (229 mm)	9 in. (229 mm)	9 in. (229 mm)	9 in. (229 mm)
<b>GROUND CLEARANCE (TRACKS)</b>	11 in. (279 mm)	11 in. (279 mm)	10 in. (254 mm)							
<b>COLORS</b>	YELLOW, BLACK									

<b>ENGINE</b>	443CC 4-STROKE
<b>CYLINDER</b>	SOHC SINGLE-CYLINDER
<b>FUEL SYSTEM</b>	EFI
<b>COOLING SYSTEM</b>	LIQUID COOLED
<b>BORE X STROKE</b>	89 X 71.2 mm
<b>COMPRESSION RATIO</b>	9.1:1
<b>START METHOD</b>	ELECTRIC START
<b>TRANSMISSION TYPE</b>	CVT AUTOMATIC
<b>FINAL DRIVE</b>	SHAFT DRIVE
<b>DIFFERENTIAL FUNCTION</b>	FRONT DIFFERENTIAL
<b>DRIVE SYSTEM TYPE</b>	ELECTRONIC 2WD/4WD/LOCK
<b>ENGINE BRAKING SYSTEM (EBS)</b>	STANDARD
<b>LENGTH</b>	106.3 in. (2,700 mm)
<b>WIDTH</b>	56.7 in. (1,440 mm)
<b>HEIGHT</b>	72.8 in. (1,849 mm)
<b>GROUND CLEARANCE</b>	10 in. (254 mm)
<b>WHEELBASE</b>	72 in. (1,829 mm)
<b>TOWING CAPACITY</b>	1,200 LB. (543 kg)
<b>DRY WEIGHT</b>	1,286 LB. (583 kg)
<b>WET WEIGHT</b>	1,332 LB. (604 kg)
<b>FUEL TANK CAPACITY</b>	8.5 GAL (32 l)
<b>RIDER CAPACITY</b>	2
<b>SUSPENSION - FRONT &amp; REAR</b>	INDEPENDENT DOUBLE A-ARM
<b>SUSPENSION TRAVEL - FRONT</b>	6.9 in. (175 mm)
<b>SUSPENSION TRAVEL - REAR</b>	6.8 in. (173 mm)
<b>BRAKE - FRONT</b>	DUAL HYDRAULIC DISC
<b>BRAKE - REAR</b>	HYDRAULIC DISC
<b>TIRE SIZE (FRONT)</b>	AT25X8-12 (DURO)
<b>TIRE SIZE (REAR)</b>	AT25X10-12 (DURO)
<b>WHEEL RIM</b>	STEEL
<b>ELECTRIC POWER STEERING</b>	YES
<b>REAR BOX STORAGE</b>	441 LB. (200 kg)
<b>HITCH</b>	STANDARD/2" RECEIVER
<b>WINCH</b>	3,000 lb.
<b>LIGHTING</b>	HIGH/LOW BEAM, LED RUNNING
<b>STORAGE</b>	UNDER HOOD, UNDER SEAT, TAILGATE, GLOVE BOX
<b>SPECIAL FEATURES</b>	12V CHARGER, FRONT BRUSHGUARD, REAR BUMPER, PASSENGER HANDHOLD, 3-POINT SAFETY BELTS, SKID PLATE, HOURS METER
<b>COLOR</b>	YELLOW, BLACK

**VISIT [ARGOXTV.COM](http://ARGOXTV.COM) FOR THE FULL MODEL SPECS**