

DOESN'T FEEL LIKE WORK.



MAGNUM PRO XTX

From point A to B to Z. The Magnum Pro XTX makes it easier to get things done around any job site. Not to mention, it is pretty darn fun driving around, from sunrise to sunset. ARGO outhustles SSV competitors by offering you more for your money. The Magnum Pro 500 XTX is equipped with super-durable painted plastics, Electronic Power Steering (EPS), 25" steel wheels on aggressive Duro tires, a rear bumper, a front brushguard and a 3,000 lb. winch — all standard, straight from the factory. All that, plus, our certified Roll-Over Safety Structure (ROPS) and three-point seatbelts. ARGO has redefined what a complete, high-quality SxS should be because we know you don't appreciate being nicked-and-dimed for everything. Let's keep it simple and straightforward because you have too much to check off on that to-do list.



MAGNUM PRO XTX HIGHLIGHTS

- 443cc EFI Liquid Cooled Single Cylinder Engine
- Automatic CV Transmission
- Electronic 2wd/4wd with Front Differential Lock
- Electronic Power Steering (EPS)
- Tilt Steering Wheel
- Double A-Arm Front and Rear Suspension
- Adjustable Pre-Load Rear Shocks
- Rear Sway Bar
- Aggressive Duro Tires
- Steel Wheels
- Digital Display with hours Meter
- Heavy-Duty Front Brushguard
- Rear Bumper
- 3,000 lb. Winch
- Rear Cargo Box with Tilt Assist
- 2" Receiver Hitch
- 1,200 lb. Towing Capacity
- Certified Roll-Over Protection Structure (ROPS)

MAGNUM TECHNOLOGY



ENGINE

The rugged 443cc 4-stroke SOHC engine comes Liquid Cooled and features Electronic Fuel Injection (EFI). Responsive and fuel efficient, this engine is ready to go to work, on and off the trail.



2WD/4WD WITH FRONT DIFFERENTIAL LOCK

Automatic CV transmission featuring high and low range, neutral, reverse and park. Being fully sealed and vented, engine braking ensures ceaseless performance in the fiercest terrain. Standard on all Magnum Pro XTX models, the electronic 2wd/4wd with front differential lock provides on-demand traction when you need it the most.



SUSPENSION

Independent double a-arm front and rear suspensions offering 6.9" (175 mm) of travel in the front and 6.8" (173 mm) of travel in the rear react instantaneously with the adjustable preload shocks to deliver a comfortable and consistent operator experience every time you ride.



CARGO BOX WITH MAT

Built for versatile applications, the utility cargo box comes equipped with a dump assist shock and a 441 lb. (200 kg) load capacity. Additionally, the cargo box is outfitted with a contoured bed mat, giving the cargo space added grip and protection.



HITCH & TOWING CAPACITY

The 2" rear receiver hitch is backed by a 1,200 lb. (543 kg) towing capacity, making it the perfect work-horse for both recreation and utility applications.



DISPLAY

Digital display with odometer, speedometer, tripmeter, RPM, transmission position, 2wd/4wd/lock indicator, fuel gauge, hours meter, temperature, low-battery, high-beam and check engine lights.



FRONTIER PRO
700 XT 8x6



AURORA PRO
800 XT 8x8



AURORA PRO
950 XT 8x8



CONQUEST PRO
800 XT 8x8



CONQUEST PRO
950 XT 8x8



CONQUEST PRO
800 XTL 8x8



CONQUEST PRO
950 XTL 8x8



CONQUEST PRO
800 XTX 8x8



CONQUEST PRO
950 XTX 8x8



MAGNUM PRO
500 XTX

ENGINE	VX 700	KX 800	VX 950	KX 800	VX 950	KX 800	VX 950	KX 800	VX 950
CYLINDER	V-TWIN	V-TWIN	V-TWIN	V-TWIN	V-TWIN	V-TWIN	V-TWIN	V-TWIN	V-TWIN
FUEL SYSTEM	EFI	EFI	EFI	EFI	EFI	EFI	EFI	EFI	EFI
COOLING	FAN COOLED	LIQUID COOLED	FAN COOLED	LIQUID COOLED	FAN COOLED	LIQUID COOLED	FAN COOLED	LIQUID COOLED	FAN COOLED
ALTERNATOR OUTPUT (MAX)	16 AMPS	40 AMPS	50 AMPS	60 AMPS	50 AMPS	60 AMPS	50 AMPS	60 AMPS	50 AMPS
CHASSIS	6X6	8X8	8X8	8X8	8X8	8X8	8X8	8X8	8X8
SERVICE BRAKES	HYDRAULIC	HYDRAULIC	HYDRAULIC	HYDRAULIC	HYDRAULIC	HYDRAULIC	HYDRAULIC	HYDRAULIC	HYDRAULIC
STEERING BRAKES	HYDRAULIC	HYDRAULIC	HYDRAULIC	HYDRAULIC	HYDRAULIC	HYDRAULIC	HYDRAULIC	HYDRAULIC	HYDRAULIC
AUTO CHAIN LUBRICATION	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD
BRAKE COOLING KIT	STANDARD	STANDARD	STANDARD	N/A	N/A	N/A	N/A	N/A	N/A
TRANSMISSION	CLASSIC W/APS	ADMIRAL W/APS	ADMIRAL W/APS	ADMIRAL	ADMIRAL	ADMIRAL	ADMIRAL	ADMIRAL	ADMIRAL
DRIVE BELT	STANDARD	STANDARD	STANDARD	HEAVY DUTY	HEAVY DUTY	HEAVY DUTY	HEAVY DUTY	HEAVY DUTY	HEAVY DUTY
FULL SKID PLATE	HEAVY DUTY	HEAVY DUTY	HEAVY DUTY	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD
BRUSHGUARD	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD
WINCH	3,500 lb. w/ SYNTHETIC ROPE	3,500 lb. w/ SYNTHETIC ROPE	3,500 lb. w/ SYNTHETIC ROPE	4,500 lb. w/ SYNTHETIC ROPE	4,500lb. w/ SYNTHETIC ROPE	4,500 lb. w/ SYNTHETIC ROPE	4,500 lb. w/ SYNTHETIC ROPE	4,500 lb. w/ SYNTHETIC ROPE	4,500 lb. w/ SYNTHETIC ROPE
FRONT RACK	STANDARD	STANDARD	STANDARD	ACCESSORY	ACCESSORY	STANDARD	STANDARD	STANDARD	STANDARD
REAR RACK	STANDARD	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
BILGE PUMP	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD
ROPS	STANDARD	STANDARD	STANDARD	ACCESSORY	ACCESSORY	STANDARD	STANDARD	STANDARD	STANDARD
REAR MESH	N/A	N/A	N/A	ACCESSORY	ACCESSORY	STANDARD	STANDARD	STANDARD	STANDARD
ROOF	N/A	STANDARD	STANDARD	ACCESSORY	ACCESSORY	STANDARD	STANDARD	STANDARD	STANDARD
POWER DUMP BOX	N/A	N/A	N/A	ACCESSORY	ACCESSORY	ACCESSORY	ACCESSORY	STANDARD	STANDARD
LOAD CAPACITY - LAND	440 lb. [200 kg]	635 lb. [288 kg]	705 lb. [320 kg]	1,210 lb. [549 kg]	1,210 lb. [549kg]	981 lb. [445 kg]	981 lb. [445 kg]	848 lb. [385 kg]	848 lb. [385 kg]
LOAD CAPACITY - WATER	240 lb. [109 kg]	435 lb. [197 kg]	505 lb. [229 kg]	510 lb. [231 kg]	510 lb. [231 kg]	281 lb. [128 kg]	281 lb. [128 kg]	148 lb. [67 kg]	148 lb. [67 kg]
TOWING CAPACITY	1,200 lb. [544 kg]	1,800 lb. [816 kg]	1,800 lb. [816 kg]	2,000 lb. [907 kg]	2,000 lb. [907 kg]	2,000 lb. [907 kg]	2,000 lb. [907 kg]	2,000 lb. [907 kg]	2,000 lb. [907 kg]
SEATING CAPACITY - LAND	2	4	4	2	2	2	2	2	2
SEATING CAPACITY - WATER	2	4	4	2	2	2	2	2	2
FUEL CAPACITY	8.5 gal. [32 L]	8.5 gal. [32 L]	8.5 gal. [32 L]	8.5 gal. [32 L]	8.5 gal. [32 L]	8.5 gal. [32 L]	8.5 gal. [32 L]	8.5 gal. [32 L]	8.5 gal. [32 L]
WATER CAPABILITY	WATER FORDING	WATER FORDING	WATER FORDING	AMPHIBIOUS	AMPHIBIOUS	WATER FORDING	WATER FORDING	WATER FORDING	WATER FORDING
WEIGHT	1,100 lb. [499 kg]	1,915 lb. [869 kg]	1,845 lb. [837 kg]	1,890 lb. [857 kg]	1,890 lb. [857 kg]	2,119 lb. [961 kg]	2,119 lb. [961 kg]	2,252 lb. [1,021 kg]	2,252 lb. [1,021 kg]
LENGTH (includes winch when standard)	103 in. [2,616 mm]	126 in. [3,200 mm]	126 in. [3,200 mm]	125 in. [3,175 mm]	125 in. [3,175 mm]	125 in. [3,175 mm]	125 in. [3,175 mm]	125 in. [3,175 mm]	125 in. [3,175 mm]
WIDTH	60 in. [1,524 mm]	60 in. [1,524 mm]	60 in. [1,524 mm]	65 in. [1,651 mm]	65 in. [1,651 mm]	65 in. [1,651 mm]	65 in. [1,651 mm]	65 in. [1,651 mm]	65 in. [1,651 mm]
HEIGHT	77 in. [1,956 mm]	77 in. [1,956 mm]	77 in. [1,956 mm]	49 in. [1,245 mm]	49 in. [1,245 mm]	80.5 in. [2,045 mm]	80.5 in. [2,045 mm]	80.5 in. [2,045 mm]	80.5 in. [2,045 mm]
AXLE BEARING EXTENSIONS	STANDARD	STANDARD	STANDARD	N/A	N/A	N/A	N/A	N/A	N/A
TIRES	ARGO XT119 25X12-9	ARGO XT119 25X12-9	ARGO XT119 25X12-9	ARGO XT117 25X12-9	ARGO XT117 25X12-9	ARGO XT119 25X12-9	ARGO XT119 25X12-9	ARGO XT119 25X12-9	ARGO XT119 25X12-9
WHEELS	STEEL BEADLOCK	STEEL BEADLOCK	STEEL BEADLOCK	STEEL BEADLOCK	STEEL BEADLOCK	STEEL BEADLOCK	STEEL BEADLOCK	STEEL BEADLOCK	STEEL BEADLOCK
GROUND CLEARANCE (TIRES)	10 in. [254 mm]	10 in. [254 mm]	10 in. [254 mm]	9 in. [229 mm]	9 in. [229 mm]	9 in. [229 mm]	9 in. [229 mm]	9 in. [229 mm]	9 in. [229 mm]
GROUND CLEARANCE (TRACKS)	11 in. [279 mm]	11 in. [279 mm]	11 in. [279 mm]	10 in. [254 mm]	10 in. [254 mm]	10 in. [254 mm]	10 in. [254 mm]	10 in. [254 mm]	10 in. [254 mm]
COLORS	YELLOW, BLACK	YELLOW, BLACK	YELLOW, BLACK	YELLOW, BLACK	YELLOW, BLACK	YELLOW, BLACK	YELLOW, BLACK	YELLOW, BLACK	YELLOW, BLACK

ENGINE	443CC 4-STROKE
CYLINDER	SOHC SINGLE-CYLINDER
FUEL SYSTEM	EFI
COOLING SYSTEM	LIQUID COOLED
BORE X STROKE	89 X 71.2 mm
COMPRESSION RATIO	9.1:1
START METHOD	ELECTRIC START
TRANSMISSION TYPE	CVT AUTOMATIC
FINAL DRIVE	SHAFT DRIVE
DIFFERENTIAL FUNCTION	FRONT DIFFERENTIAL
DRIVE SYSTEM TYPE	ELECTRONIC 2WD/4WD /LOCK
ENGINE BRAKING SYSTEM (EBS)	STANDARD
LENGTH	106.3 in. [2,700 mm]
WIDTH	56.7 in. [1,440 mm]
HEIGHT	72.8 in. [1,849 mm]
GROUND CLEARANCE	10 in. [254 mm]
WHEELBASE	72 in. [1,829 mm]
TOWING CAPACITY	1,200 LB. [543 kg]
DRY WEIGHT	1,286 LB. [583 kg]
WET WEIGHT	1,332 LB. [604 kg]
FUEL TANK CAPACITY	8.5 GAL [32 l]
RIDER CAPACITY	2
SUSPENSION - FRONT & REAR	INDEPENDENT DOUBLE A-ARM
SUSPENSION TRAVEL - FRONT	6.9 in. [175 mm]
SUSPENSION TRAVEL - REAR	6.8 in. [173 mm]
BRAKE - FRONT	DUAL HYDRAULIC DISC
BRAKE - REAR	HYDRAULIC DISC
TIRE SIZE (FRONT)	AT25X8-12 [DURO]
TIRE SIZE (REAR)	AT25X10-12 [DURO]
WHEEL RIM	STEEL
ELECTRIC POWER STEERING	YES
REAR BOX STORAGE	441 LB. [200 kg]
HITCH	STANDARD/2" RECEIVER
WINCH	3,000 lb.
LIGHTING	HIGH/LOW BEAM, LED RUNNING
STORAGE	UNDER HOOD, UNDER SEAT, TAILGATE, GLOVE BOX
SPECIAL FEATURES	12V CHARGER, FRONT BRUSHGUARD, REAR BUMPER, PASSENGER HANDHOLD, 3-POINT SAFETY BELTS, SKID PLATE, HOURS METER
COLOR	YELLOW, BLACK

VISIT [ARGOXTV.COM](https://www.argoxtv.com) FOR THE FULL MODEL SPECS