

The CENTAUR 8x8 FIRE CHIEF for Off-Road Performance



APPLICATIONS

- Firefighting & Prevention
- Search & Rescue
- Emergency Medical Services and Crew Transport
- Disaster & HAZMAT Response
- Support Vehicle in Difficult Terrain

FEATURES & CAPABILITIES

- Very Low Ground Pressure
- Operates in Flooded Areas
- Crosses Deep Mud and Marshy Terrain
- Travels Over Deep Snow and Ice
- High Altitude Performance
- Overcomes Obstacles and Rocky Terrain
- Hauls Trailers and Supplies



Fording depth of 26" (660 mm)



Remote Disaster Response



Operation in -40°C (-40°F)



CET Fire Pump



75 ft, 3/4" Booster Hose



JUNKIN Rescue Basket/Stretcher

Centaur 954 DT Specifications	
Engine	DM 954 DT (Turbo Diesel) Briggs & Stratton Daihatsu, 3 cylinder, liquid cooled 952 cc displacement 34 hp @ governed 3800 rpm 58 ft./lbs @ 2400 rpm
Speed	28 mph (45 km/h)
Brakes	Hydraulic disc brakes
Electronics / Aux.	960 CCA 12V battery, 60 Amp alternator, dash mounted glow -plug-on & water-in-fuel indicators 4000 lb (1814 kg) WARN winch 30 W siren Whelen LED Ligh package
Capacity	Payload 1,500 lbs (680 kg), Towing 2,000 lbs (907 kg)

Fire Apparatus Specifications	
Water Tank	Capacity 80 US Gal. (300 L) custom fit, removable poly tank
Foam Tank	5 US Gal. (19 L)
Foam System	Scotty Model 4071, discharge manifold flowing 15, 30, 50 & 70 Gal./minute 1% foam solution at specified flows
Hose	75 ft, 3/4" Booster hose
Pump	Honda 6.5 HP, 4 stroke engine, fuelled by 1.5 Gal. tank 2 stage centrifugal pump CET Fire Pump 50 Gal./ minute @ 100 psi and 20 Gal./minute @ 150 psi Continuous operation acting as transfer pump with static supply
Rescue Basket	JUNKIN basket - 500 lb rating

Please contact us for more details about customized add-on solutions.



220 Bergey Court, New Hamburg ON, Canada N3A 2J5

Toll Free: **1-877-274-6288**

Tel: (519) 662-4000 Fax: (519) 662-2421

Amphibious UTV

www.ARGOutv.com/firechief



MIX
Paper from
responsible sources
FSC* C023070