
ALL TERRAIN • AMPHIBIOUS • ALL SEASON



Upgraded front and rear seat cushions

Easy removable hood rack WARN Winch

Bilge pump

BREAKUP

> / Robust brushguard

Enhanced exterior lighting package



Interior lighting package



Easy removable hood rack



Exterior lighting package



12V / Dual USB power outlet



Right and left entry step



Removable, fold down rear rack

EXTREME TERRAIN VEHICLE SOLUTIONS

SPECIFICATIONS FOR ARGO SCOUT 6X6


Engine		Kohler Command Pro
Engine Warranty		3 year
Туре		4 cycle OHV V-Twin gasoline EFI engine, electronic ignition, full pressure lubrication and oil filter
Horsepower*		23
Displacement		747cc
Cooling		Air Cooled
Starting		Electric
Brakes		Hydraulic
Steering		One-piece, ergonomic handlebar. Steering control features hand brake. For safety and ease of handling, the ARGO steering transmission provides continuous torque to all axles.
Controls		Right-hand twist grip throttle. Light switch, ignition switch .
Clutch		Belt-driven, Continuously Variable Transmission (CVT) maximizes engine power to the transmission.
Transmission		Planetary 6
Drive System		Roller chains drive machined sprockets that are spline-fit onto 1 ¹ /4" diameter axles and are protected with triple-sealed greaseable bearings.
Frame		Formed steel channel construction, welded for high strength and durability. Protected with Bonderite® M-PP 930™ epoxy-acrylic autodeposition coating.
Body		Vacuum formed High Molecular Weight Polyethylene
Full Skid Plate		Standard
Load Capacity ¹	On Land	600 lb. (270 kg) total
	On Water	400 lb. (180 kg) total
Towing Capacity ²		1,200 lb. (544 kg)
Seating Capacity		2 persons
Fuel Capacity		7.1 US gallons (27 litres) See-through polyethylene fuel tank. 8 hrs. operation $^{\rm 3}$
Speed ⁴		22 mph (35 km per hour) on land, 3 mph (5 km per hour) on water $^{\rm 5}$
Shipping Weight		990 lb. (449 kg)
Dimensions (L X W X H)		102 x 58 x 52.5" (2,591 x 1,473 x 1,334 mm)
Axle Bearing Extensions		Standard
Instrumentation		LCD Digital Gauge Cluster: Speedometer, Odometer, Voltmeter, Hour Meter, Tachometer, Low Oil Pressure and Parking Brake Reminder Lights
Tires		ARG0 AT189 24x10.00-8NHS
Tires		
Tires Ground Pre	ssure	1.7 psi (13.5 kPa) using tires 0.67 psi (4.6 kPa) using tracks
	rssure Tires	1.7 psi (13.5 kPa) using tires 0.67 psi (4.6 kPa) using tracks 9.5" (240 mm)
Ground Pre		


The new 2016 ARGO Scout 6x6 is a hunter's best weapon and features a number of unique options as standard equipment including:

- Upgraded front and rear seat cushions as well as a front seat backrest pad featuring refined stitching and custom embossing of the ARGO logo
- Easy removable fold down rear rack for extra cargo storage
- Hood rack capable of carrying cargo and small game out of the bush
- Robust brushguard provides outstanding protection for the front end of the vehicle, absorbing impacts from off-road hazards such as brush, branches, and more
- Entry steps to assist in vehicle entry and exit when outfitted with gear, backpack and guns
- Dual USB power outlet, for riders to charge their phones, play digital media and utilize their GPS
- Enhanced lighting package featuring dual high power floodlights
- Interior lighting package to illuminate front driving and passenger area, vehicle console and rear cargo area
- Bilge pump
- 3,500 lb. (1,588 kg) Warn Winch

DIMENSIONS

Dimensions are approximate and dependent on final build specification.





AVAILABLE ARGO COLOR Colors are reproduced with great care, but may vary slightly on actual vehicles.

Safety!

...always in Season!



tread lightly!

ON LAND AND WATER



220 Bergey Court, New Hamburg ON, Canada N3A 2J5 Toll Free: **1-877-274-6288** Tel: (519) 662-4000 Fax: (519) 662-2421 www.ARGOxtv.com/argo-scout-6x6

- Capacity includes occupants, cargo, outboard motor and fuel, and installed accessories. Max. outboard motor size 7.4 kW (9.9 hp).
 Towing capacity is approximate and depends on type of surface, load on vehicle as well as incline.
- 2 Towing capacity is approximate and depends on type of surface, load on vehicle as well as incline. Max Hitch Tongue Load (when equipped with hitch) 100 lb. (45 kg) for all models.
- 3 Fuel consumption depends on load and operating conditions.
- 4 All speeds are approximate and depend on conditions.
- 5 Always wear approved Personal Floatation Device (PFD) when operating in water or on ice.
- 6 Planetary differential transmission with High and Low range; Forward, Neutral, Reverse. * Per SAE J1940

Some vehicle applications shown are for demonstration purposes, originating from third parties and not available from ARGO. In all cases vehicle load limits have been considered. For safety, always wear approved helmets and eye protection. When operating in water, always wear approved Personal Floatation Devices. Always remain seated while in the ARGO. When equipped with tracks, Scout models are not fully amphibious, however water crossing is possible with a fording depth of 26" (660 mm).678-027 • Printed in Canada 11/2015





